

HYDRAULIC

HYDRAULICOILS

HUILES HYDRAULIQUES



The POWER HYDRAULIC RANGE meets the requirements of most hydraulic systems. To find out which oil to use, consult the engine manual. If you cannot find the product you are looking for, please contact your POWER dealer or send an email to info@power-oil.be for advice



MINIMAL ORDER QUANTITY

- In 1, 4 and 5 Liter cans : 1 palet per product and package
- In 20 L cans and drums of 60 and 190-210 Liter : per piece

QUANTITÉ MINIMALE À COMMANDER

- En bidons de 1, 4 et 5 Litres : 1 palette par produit et conditionnement
- En bidons de 20 Litres et fûts de 60 et 190-210 Litres : par pièce

HYDRAULICOILS

HYDRAULIC

POWER SH ISO HYDRAULIC OIL		
	viscosity <i>viscosité</i>	description
High Pressure (HP) DIN 51524-2 HLP	10, 15, 22, 32, 46, 68, 100, 150	Specifically designed to meet the requirements of the most important manufacturers of hydraulic equipment. It contains anti-wear, anti-oxidant, anti-corrosion and anti-foam additives.
POWER HV HYDRAULIC OIL		
	viscosity <i>viscosité</i>	description
high viscosity index (HVI) DIN: 51524 Part 3 HVLP	15, 22, 32, 46, 68	A high viscosity index paraffinic oil, based on selected ingredients, specifically intended for use in hydraulic circuits. Superior performance in keeping the system clean by reducing the formation of deposits. It also demonstrates good filterability, water separation , and quick air release.
POWER ZF HYDRAULIC OIL		
	viscosity <i>viscosité</i>	description
zinc-free (ZF) DIN 51524-2 HLP	46, 68	A high-grade zinc-free EP hydraulic oil based on selected solvent refined base oils having a natural viscosity index.

CHECK OUT
OUR WEBSITE!



+49 176 22914621

Renacompanyoil@gmail.com

HEINRICH-HERTZ-STRASSE | 11 34189 KASSEL